



TP-Link Archer C80 draadloze router Gigabit Ethernet Dual-band (2.4 GHz / 5 GHz) Zwart

Merk : TP-Link

Artikelcode: ARCHER C80

Productnaam : Archer C80

TP-Link Archer C80. Type WAN-aansluiting: RJ-45. Wifi-band: Dual-band (2.4 GHz / 5 GHz), Wifi-standaard: Wi-Fi 5 (802.11ac), WLAN gegevensoverdrachtsnelheid (max): 1300 Mbit/s. Interfacetype Ethernet LAN: Gigabit Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s, Bekabelingstechnologie: 10/100/1000Base-T(X). Ondersteunde beveiligingsalgoritmen: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Type product: Router om neer te zetten, Kleur van het product: Zwart, LED-indicatoren: LAN, Stroom, Status, WLAN, WPS



WAN-verbinding		Protocollen	
Ethernet WAN *	✓	DHCP client	✓
SIM-kaartsleuf *	✗	DHCP server	✓
Type WAN-aansluiting	RJ-45	Universal Plug and Play (UPnP)	✓
Draadloos LAN		Design	
Wifi-band *	Dual-band (2.4 GHz / 5 GHz)	Kleur van het product	Zwart
Wifi-standaard *	Wi-Fi 5 (802.11ac)	Ophangstelsysteem voor aan de muur	✓
WLAN gegevensoverdrachtsnelheid (max) *	1300 Mbit/s	LED-indicatoren	LAN, Stroom, Status, WLAN, WPS
Wi-Fi-standaarden	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Aan/uitschakelaar	✓
WLAN gegevensoverdrachtsnelheid (eerste band)	1300 Mbit/s	Type product *	Router om neer te zetten
Netwerk		Inhoud van de verpakking	
Ethernet LAN *	✓	Meegeleverde kabels	AC, LAN (RJ-45)
Interfacetype Ethernet LAN *	Gigabit Ethernet	Inclusief AC-adapter	✓
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Snelle installatiehandleiding	✓
Bekabelingstechnologie	10/100/1000Base-T(X)	Antenne	
Netwerkstandaard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Antenne-ontwerp *	Extern
Port forwarding	✓	Antennas quantity	4
Dynamic DNS (DDNS)	✓	Afneembare antennes	✗
Poorten & interfaces		Zendvermogen	CE: <20dBm(2.4 GHz), <23dBm(5.15 GHz~5.25 GHz), FCC:<30dBm(2.4 GHz & 5 GHz)
Aantal Ethernet LAN (RJ-45)-poorten *	5	Energie	
USB-poort *	✗	Type stroombron *	DC
Geheugenkaart slot(s)	✗	Spanning	12 V
		Eisen aan de omgeving	
		Bedrijfstemperatuur (T-T)	0 - 40 °C
		Temperatuur bij opslag	-40 - 70 °C

Poorten & interfaces		Eisen aan de omgeving	
Aansluiting voor netstroomadapter	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Beheerfuncties		Luchtvochtigheid bij opslag	5 - 90 procent
Reset button	✓	Minimale systeemeisen	
WPS Push Button Security	✓	Ondersteunde browser	Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0
Beveiliging			Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows NT, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Ondersteunde beveiligingsalgoritmen	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Ondersteunt Windows	
Firewall	✓	Ondersteunt Linux	✓
Toegang voor gasten	✓	Ondersteunt Mac-besturingssysteem	MacOS
Access Control List (ACL)	✓	Mac-compatibiliteit	✓
Stateful Packet Inspection (SPI)	✓	Verpakking	
MAC adres filtering	✓	Breedte verpakking	350 mm
DMZ support	✓	Diepte verpakking	240 mm
		Hoogte verpakking	82 mm
		Gewicht verpakking	800 g



6935364088873



1210002615976

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.